

Bedroom Sounders

24V Low Frequency

The flush mount Bedroom Sounder is EN54-3 and CPD approved as an indoor low current 2 tone sounder for the fire alarm market. It is designed to be aesthetically unobtrusive in hotel bedrooms, restaurants and residential environments, by being able to fit into a 25mm deep 1 gang flush or surface mounted patress box. The FM Bedroom Sounder comes in white or red flame retardant ABS.

This Bedroom Sounder complement a comprehensive range which have been designed and built with quality, reliability and the requirements of the end user foremost in mind, thereby allowing a wide spectrum of Fire and Security applications to be serviced.



- Low current consumption

- Dual sound options selected via a jumper switch

- Both flush and surface mounted

- Robust terminal connectors to accommodate up to 2.5mm conductors

- Flush mount sounder is CPD approved 0832-CPD-0477 and LPCB approved to EN54-3 Certificate No.715a /06



Bedroom Sounders

24V Low Frequency

product data sheet



Specification

Dimensions:	85mm x 85mm x 30mm deep
Typical Current Consumption:	7mA
Max Volume:	90dBA @ 1m (typical)
Frequency:	800-970Hz (@ 9Hz)
Fast Sweep:	850Hz
Continuous:	24 Volts DC
Input:	Surface or flush mounted using 25mm deep patress box
Installation:	Red or white, flame retardant ABS
Colours:	2 in, 2 out, each 2.5mm max
Connections:	

FM (Flush Mount) Bedroom Sounder



Every care has been taken in the preparation of this product release but no liability whatsoever can be accepted for the use of the information contained therein. Hosiden Besson Ltd reserve the right to change or amend any design features in line with our policy of continuing development and improvement.